RECEIVED
CENTRAL FAX CENTER
DEC 0 2 2005

capable of use in extreme environments or may be soft and comfortable against the skin. Regardless, it is desirable that the material of the pillow cover be suitable for washing. Example materials include cotton, nylon, [[p]]Polartec, jersey knit, polyester, and fleece. The bottom, left, and right edges of the front and back cloths are seamed together. Of course, if only one sheet of material is used, one of the seams is substituted with a fold of the material.

Please replace the originally filed paragraph starting on page 10, line 7, with the following:

In figure 5, a first airflow path 352 is shown at the interface between wrap 346 and first peripheral portion 336 of first panel 302. Also in figure 5, a second airflow path 354 is shown at the interface between wrap 346 and second peripheral portion 338 of second panel 330. Additionally, a plurality of needle holes 356 are shown extending through flange 326 of pillow 300. With reference to figure 5, it will be appreciated that central portion 324 of first panel 302 and central portion 324 of ~~first panel 302~~ second panel 330 are free of needle holes in the embodiment of figure 4 and figure 5.

PAGE 1/12 * RCVD AT 12/2/2005 5:07:06 PM [Eastern Standard Time] * SVR:USPTO-EFXRF-6/26 * DNIS:2738300 * CSID: * DURATION (mm-ss):02-50